SAFETY DATA SHEET



1. Identification

| 1. Identification | | | |
|----------------------------------|---|---------------|-------------|
| Product identifier | Motor Medic Thrust Starting | Fluid | |
| Other means of identification | | | |
| SDS number | M3815 | | |
| Part No. | M3815 | | |
| Tariff code | 2909.11.0000 | | |
| Recommended use | Starting Fluid | | |
| Recommended restrictions | None known. | | |
| Manufacturer/Importer/Supplier/I | Distributor information | | |
| Manufacturer | | | |
| Company name | RSC Chemical Solutions | | |
| Address | 600 Radiator Road Indian Trail, NC 28079 | | |
| | United States | | |
| Telephone | Customer Service: | (704) 821-764 | 43 |
| | Technical: | (704) 684-18 | 11 |
| Website E-mail | www.rscbrands.com | | |
| E-mail Emergency phone number | sds@rscbrands.com Emergency Telephone: | (303) 623-571 | 16 |
| Emergency phone number | Emergency Contact: | RMPDC (877- | |
| 0 Hazard(a) identification | | | |
| 2. Hazard(s) identification | | | _ |
| Physical hazards | Flammable aerosols | | Category 1 |
| Health hazards | Acute toxicity, oral | | Category 4 |
| | Skin corrosion/irritation | | Category 2 |
| | Serious eye damage/eye irritati | ion | Category 2B |
| | Carcinogenicity | | Category 1B |
| | Specific target organ toxicity, si | | |
| | Specific target organ toxicity, re exposure | epeated | Category 2 |
| Environmental hazards | Hazardous to the aquatic environ hazard | onment, acute | Category 1 |
| | Hazardous to the aquatic environ long-term hazard | onment, | Category 1 |
| OSHA defined hazards | Not classified. | | |
| Label elements | | | |
| | | . 🔺 | |



Signal word Hazard statement Danger

Extremely flammable aerosol. Harmful if swallowed. Causes skin irritation. Causes eye irritation. May cause drowsiness or dizziness. May cause cancer. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.

| Precautionary statement | |
|--|---|
| Prevention | Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection. |
| Response | If swallowed: Call a poison center/doctor if you feel unwell. If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Rinse mouth. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse. Collect spillage. |
| Storage | Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. |
| Disposal | Dispose of contents/container in accordance with local/regional/national/international regulations. |
| Hazard(s) not otherwise classified (HNOC) | None known. |
| Supplemental information | 81.58% of the mixture consists of component(s) of unknown acute oral toxicity. 26.34% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 26.34% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment. |

3. Composition/information on ingredients

Mixtures

| Chemical name | Common name and synonyms | CAS number | % |
|---|--------------------------|------------|-----------|
| Heptane | | 142-82-5 | 70 - < 80 |
| ETHANE, 1,1'-OXYBIS- | | 60-29-7 | 10 - < 20 |
| Carbon Dioxide | | 124-38-9 | 5 - < 10 |
| Distillates (petroleum), Hydrotreated Light Naphthenic | | 64742-53-6 | < 1 |
| Hydrotreated Heavy Naphthenic Distillate (petroleum) | | 64742-52-5 | < 1 |

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

| Inhalation | Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. |
|--|--|
| Skin contact | Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse. |
| Eye contact | Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists. |
| Ingestion | Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical advice/attention if you feel unwell. |
| Most important symptoms/effects, acute and delayed | May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. Skin irritation. May cause redness and pain. |
| Indication of immediate medical attention and special treatment needed | Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed. |
| General information | IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. |
| 5. Fire-fighting measures | |

| Suitable extinguishing media | Powder. Alcohol resistant foam. Carbon dioxide (CO2). |
|------------------------------|--|
| Unsuitable extinguishing | Do not use water jet as an extinguisher, as this will spread the fire. |
| media | |

| Specific hazards arising from the chemical | Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed. |
|---|---|
| Special protective equipment and precautions for firefighters | Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. |
| Fire fighting equipment/instructions | Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. |
| Specific methods | Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes. |
| General fire hazards | Extremely flammable aerosol. |
| 6. Accidental release meas | sures |
| Personal precautions, protective equipment and emergency procedures | Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. |
| Methods and materials for containment and cleaning up | Refer to attached safety data sheets and/or instructions for use. Keep combustibles (wood, paper, oil, etc.) away from spilled material. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. |
| | Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS. |
| Environmental precautions | Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases. |
| 7. Handling and storage | |
| Precautions for safe handling | Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices. |
| Conditions for safe storage, | Level 3 Aerosol. |
| including any incompatibilities | Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS). |

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components | Туре | Value | Form | |
|--|------|------------|-------|--|
| Carbon Dioxide (CAS 124-38-9) | PEL | 9000 mg/m3 | | |
| | | 5000 ppm | | |
| Distillates (petroleum), Hydrotreated Light Naphthenic (CAS 64742-53-6) | PEL | 5 mg/m3 | Mist. | |
| | | 2000 mg/m3 | | |

| Components | for Air Contaminants (29 CFR 1910.1000) Type | Value | Form |
|--|--|--|---|
| | | 500 ppm | |
| ETHANE, 1,1'-OXYBIS- (CAS 60-29-7) | PEL | 1200 mg/m3 | |
| Heptane (CAS 142-82-5) | PEL | 400 ppm 2000 mg/m3 | |
| | | 500 ppm | Mint |
| Hydrotreated Heavy Naphthenic Distillate (petroleum) (CAS 64742-52-5) | PEL | 5 mg/m3 | Mist. |
| | | 2000 mg/m3 500 ppm | |
| US. ACGIH Threshold Limi | | | _ |
| Components | Туре | Value | Form |
| Carbon Dioxide (CAS 124-38-9) | STEL | 30000 ppm | |
| | TWA | 5000 ppm | |
| Distillates (petroleum), Hydrotreated Light Naphthenic (CAS 64742-53-6) | TWA | 5 mg/m3 | Inhalable fraction. |
| ETHANE, 1,1'-OXYBIS- (CAS 60-29-7) | STEL | 500 ppm | |
| | TWA | 400 ppm | |
| Heptane (CAS 142-82-5) | STEL | 500 ppm | |
| | TWA | 400 ppm | |
| Hydrotreated Heavy Naphthenic Distillate (petroleum) (CAS 64742-52-5) | TWA | 5 mg/m3 | Inhalable fraction. |
| US. NIOSH: Pocket Guide Components | to Chemical Hazards Type | Value | Form |
| Carbon Dioxide (CAS | STEL | 54000 mg/m3 | |
| 124-38-9) | | 30000 ppm | |
| | TWA | 9000 mg/m3 | |
| | | 5000 ppm | |
| Distillates (petroleum), Hydrotreated Light Naphthenic (CAS 64742-53-6) | Ceiling | 1800 mg/m3 | |
| 01712000) | STEL | 10 mg/m3 | Mist. |
| Heptane (CAS 142-82-5) | Ceiling | 1800 mg/m3 440 ppm | |
| | TWA | 350 mg/m3 85 ppm | |
| Hydrotreated Heavy Naphthenic Distillate (petroleum) (CAS 64742-52-5) | Ceiling | 1800 mg/m3 | |
| | STEL | 10 mg/m3 | Mist. |
| logical limit values | No biological exposure limits noted for the ing | redient(s). | |
| propriate engineering trols | Good general ventilation (typically 10 air chan should be matched to conditions. If applicable or other engineering controls to maintain airbo exposure limits have not been established, ma wash facilities and emergency shower must b | e, use process enclosu orne levels below recor aintain airborne levels | res, local exhaust ventilation nmended exposure limits. to an acceptable level. Eye |

Individual protection measures, such as personal protective equipment

| · Eve/feeee eveteetien | Chemical receivator with expense contridge and full federations |
|-----------------------------------|---|
| Eye/face protection | Chemical respirator with organic vapor cartridge and full facepiece. |
| Skin protection | |
| Hand protection | Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier. |
| Other | Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. |
| Respiratory protection | Chemical respirator with organic vapor cartridge and full facepiece. |
| Thermal hazards | Wear appropriate thermal protective clothing, when necessary. |
| General hygiene considerations | When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. |

9. Physical and chemical properties

| Appearance | Liquid. Clear. |
|--|-----------------------------------|
| Physical state | Liquid. |
| Form | Aerosol. |
| Color | Colorless |
| Odor | Ester-like. |
| Odor threshold | Not available. |
| рН | Not available. |
| Melting point/freezing point | -189.94 °F (-123.3 °C) estimated |
| Initial boiling point and boiling range | -109.3 °F (-78.5 °C) estimated |
| Flash point | -1.0 °F (-18.3 °C) Tag Closed Cup |
| Evaporation rate | Not available. |
| Flammability (solid, gas) | Not applicable. |
| Upper/lower flammability or expl | losive limits |
| Flammability limit - lower (%) | 1.9 % estimated |
| Flammability limit - upper (%) | 36.5 % estimated |
| Explosive limit - lower (%) | Not available. |
| Explosive limit - upper (%) | Not available. |
| Vapor pressure | 4083.55 hPa estimated |
| Vapor density | Not available. |
| Relative density | Not available. |
| Solubility(ies) | |
| Solubility (water) | Partial Solubility |
| Partition coefficient (n-octanol/water) | Not available. |
| Auto-ignition temperature | 320 °F (160 °C) estimated |
| Decomposition temperature | Not available. |
| Viscosity | Not available. |
| Other information | |
| Density | 5.75 lbs/gal |
| Explosive properties | Not explosive. |
| Flammability class | Flammable IA estimated |
| Heat of combustion (NFPA 30B) | 30.83 kJ/g estimated |
| Oxidizing properties | Not oxidizing. |
| Percent volatile | 18.42 % estimated |
| Specific gravity | 0.69 |
| | |

VOC (Weight %) 93 %

10. Stability and reactivity

| Reactivity | The product is stable and non-reactive under normal conditions of use, storage and transport. |
|---------------------------------------|---|
| Chemical stability | Material is stable under normal conditions. |
| Possibility of hazardous reactions | No dangerous reaction known under conditions of normal use. |
| Conditions to avoid | Avoid temperatures exceeding the flash point. Contact with incompatible materials. |
| Incompatible materials | Strong oxidizing agents. Aluminum. |
| Hazardous decomposition products | No hazardous decomposition products are known. |

11. Toxicological information

Information on likely routes of exposure

| Inhalation | May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful. |
|--|---|
| Skin contact | Causes skin irritation. |
| Eye contact | Causes eye irritation. |
| Ingestion | Harmful if swallowed. |
| Symptoms related to the physical, chemical and toxicological characteristics | Headache. May cause drowsiness and dizziness. Nausea, vomiting. Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. Skin irritation. May cause redness and pain. |

Information on toxicological effects

| Acute toxicity | Harmful if swallowed. Narcotic effects. | |
|--------------------------------------|--|---|
| Components | Species | Test Results |
| ETHANE, 1,1'-OXYBIS- (CAS 60- | -29-7) | |
| Acute | | |
| Inhalation | | |
| LC50 | Rat | 32000 ppm, 4 Hours |
| Oral | | |
| LD50 | Rat | 3230 - 3920 mg/kg |
| Heptane (CAS 142-82-5) | | |
| <u>Acute</u> | | |
| Inhalation | | |
| LC50 | Rat | 103 mg/l, 4 Hours |
| LD50 | Mouse | 75 mg/l, 2 Hours |
| * Estimates for product may I | be based on additional component data not | shown. |
| Skin corrosion/irritation | Causes skin irritation. | |
| Serious eye damage/eye irritation | Causes eye irritation. | |
| Respiratory or skin sensitizatio | n | |
| Respiratory sensitization | Not a respiratory sensitizer. | |
| Skin sensitization | This product is not expected to cause skin sensitization. | |
| Germ cell mutagenicity | No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic. | |
| Carcinogenicity | May cause cancer. | |
| IARC Monographs. Overall | Evaluation of Carcinogenicity | |
| ETHANE, 1,1'-OXYBIS- | • • | sifiable as to carcinogenicity to humans. |
| OSHA Specifically Regulate | ed Substances (29 CFR 1910.1001-1050) | |
| Not listed. | | |
| •• | ogram (NTP) Report on Carcinogens lydrotreated Light Naphthenic Known To | |
| | | Be Human Carcinogen. |

| Hydrotreated Heavy Napl | nthenic Distilla | te (petroleum) | Known To Be Human Ca | arcinogen. |
|---|---|--|--|--|
| (CAS 64742-52-5) | This product | t is not ovposted | to cause reproductive or de | avalapmental offects |
| Reproductive toxicity Specific target organ toxicity - | This product is not expected to cause reproductive or developmental effects. May cause drowsiness and dizziness. | | | |
| single exposure | - | | JIZZII1633. | |
| Specific target organ toxicity - repeated exposure | Not classifie | d. | | |
| Aspiration hazard | Not an aspir | ation hazard. | | |
| Chronic effects | Prolonged in | nhalation may be | harmful. | |
| 12. Ecological information | 1 | | | |
| Ecotoxicity | Very toxic to | aquatic life with | long lasting effects. | |
| Components | | Species | | Test Results |
| ETHANE, 1,1'-OXYBIS- (CAS | 60-29-7) | | | |
| Aquatic | | Fathers of using | | |
| | LC50 | Falnead minr | now (Pimephales promelas) | 2560 mg/l, 96 hours |
| Heptane (CAS 142-82-5) Aquatic | | | | |
| - | LC50 | Mozambique mossambica) | tilapia (Tilapia) | 375 mg/l, 96 hours |
| * Estimates for product may b Persistence and degradability Bioaccumulative potential | | | ent data not shown. egradability of this product. | |
| Partition coefficient n-octan | ol / water (lor | | | |
| ETHANE, 1,1'-OXYBIS- Heptane | | y Row) | 0.89 4.66 | |
| Mobility in soil | No data ava | ilable. | | |
| Other adverse effects | | | | letion, photochemical ozone creation I) are expected from this component. |
| 13. Disposal consideration | าร | | | |
| Disposal instructions | Collect and under press sewers/wate | ure. Do not punc er supplies. Do no | ture, incinerate or crush. Do ot contaminate ponds, wate | censed waste disposal site. Contents o not allow this material to drain into erways or ditches with chemical or used with local/regional/national/international |
| Local disposal regulations | Dispose in a | ccordance with | all applicable regulations. | |
| Hazardous waste code | The waste c disposal cor | | ssigned in discussion betwe | een the user, the producer and the waste |
| Waste from residues / unused products | | dues. This mater | | containers or liners may retain some e disposed of in a safe manner (see: |
| Contaminated packaging | emptied. En | | hould be taken to an appro | blow label warnings even after container is ved waste handling site for recycling or |
| 14. Transport information | | | | |
| DOT | | | | |
| UN number UN proper shipping name | Not available Consumer C | - | | |
| Transport hazard class(es) | | | | |
| Class Subsidiemuriek | ORM-D | | | |
| Subsidiary risk Packing group Environmontal bazards | - Not applicat | ble. | | |

Marine pollutantYesSpecial precautions for userRead safety instructions, SDS and emergency procedures before handling.

Environmental hazards

| | Special provisions | T75, TP5 |
|-----|-----------------------------|---|
| | Packaging exceptions | 306 |
| | Packaging non bulk | 304 |
| | Packaging bulk | 314, 315 |
| ΙΑΤ | | |
| | UN number | UN1950 |
| | UN proper shipping name | Aerosols, Flammable (Starting Fluid) |
| | Transport hazard class(es) | Acrosols, Flammable (Otaliting Flaid) |
| | | |
| | Class | 2.1 |
| | Subsidiary risk | - |
| | Packing group | Not applicable. |
| | Environmental hazards | Yes |
| | ERG Code | 9L |
| | | Read safety instructions, SDS and emergency procedures before handling. |
| | Other information | |
| | Passenger and cargo | Allowed. |
| | aircraft | |
| | Cargo aircraft only | Allowed. |
| IMD | G | |
| | UN number | UN1950 |
| | UN proper shipping name | Aerosols (ILimited QtY) |
| | Transport hazard class(es) | |
| | Class | 2.1 |
| | Subsidiary risk | - |
| | Packing group | Not applicable. |
| | Environmental hazards | |
| | | Yes |
| | Marine pollutant | |
| | EmS | F-D, S-U |
| - | | Read safety instructions, SDS and emergency procedures before handling. |
| | nsport in bulk according to | Not established. |
| | ex II of MARPOL 73/78 and | |
| | IBC Code | |
| IAT | A; IMDG | |



Marine pollutant



General information

IMDG Regulated Marine Pollutant. DOT Regulated Marine Pollutant.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

| TSCA Section 12(b) Export I | Notification (40 CFR 707, Su | ubpt. D) |
|--|---|---|
| Not regulated. CERCLA Hazardous Substa | nce List (40 CFB 302.4) | |
| ETHANE, 1,1'-OXYBIS- (Heptane (CAS 142-82-5) | | Listed. Listed. |
| SARA 304 Emergency release | se notification | |
| Not regulated. OSHA Specifically Regulated | d Substances (29 CFR 1910 |).1001-1050) |
| Not listed. | | |
| Superfund Amendments and Re | Immediate Hazard - Yes | SARA) |
| Hazard categories | Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No | |
| SARA 302 Extremely hazard Not listed. | ous substance | |
| SARA 311/312 Hazardous chemical | No | |
| SARA 313 (TRI reporting) Not regulated. | | |
| Other federal regulations | | |
| Clean Air Act (CAA) Section | 112 Hazardous Air Pollutar | nts (HAPs) List |
| Not regulated. | | |
| Clean Air Act (CAA) Section | | Prevention (40 CFR 68.130) |
| ETHANE, 1,1'-OXYBIS- (| | |
| Safe Drinking Water Act (SDWA) | Not regulated. | |
| Chemical Code Number | | sential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and |
| ETHANE, 1,1'-OXYB | | 6584 Exampt Chamical Mixtures (21 CEP 1210 12(a)) |
| ETHANE, 1,1'-OXYB | | Exempt Chemical Mixtures (21 CFR 1310.12(c)) 35 %WV |
| DEA Exempt Chemical I | , | 33 /8₩₩ |
| ETHANE, 1,1'-OXYB | | 6584 |
| US state regulations | - (, | |
| - | ubstances. CA Department of | of Justice (California Health and Safety Code Section 11100) |
| Not listed. | | ······································ |
| US. California. Candidate Ch (a)) | emicals List. Safer Consur | mer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. |
| Hydrotreated Heavy Naph | vdrotreated Light Naphthenic hthenic Distillate (petroleum) | |
| US. Massachusetts RTK - Su | | |
| Carbon Dioxide (CAS 124 Distillates (petroleum), Hy ETHANE, 1,1'-OXYBIS- (Heptane (CAS 142-82-5) | vdrotreated Light Naphthenic | (CAS 64742-53-6) |
| | nthenic Distillate (petroleum) Community Right-to-Know | |
| Carbon Dioxide (CAS 124 ETHANE, 1,1'-OXYBIS- (Heptane (CAS 142-82-5) | CAS 60-29-7) | |
| US. Pennsylvania Worker an | nd Community Right-to-Kno | ow Law |
| Carbon Dioxide (CAS 124 | | |
| ETHANE, 1,1'-OXYBIS- (| | |
| Heptane (CAS 142-82-5) US. Rhode Island RTK | | |
| ETHANE, 1,1'-OXYBIS- (| CAS 60-29-7) | |
| | | |

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

| Country(s) or region | Inventory name | On inventory (yes/no)* |
|-----------------------------|---|------------------------|
| Australia | Australian Inventory of Chemical Substances (AICS) | Yes |
| Canada | Domestic Substances List (DSL) | Yes |
| Canada | Non-Domestic Substances List (NDSL) | No |
| China | Inventory of Existing Chemical Substances in China (IECSC) | Yes |
| Europe | European Inventory of Existing Commercial Chemical Substances (EINECS) | Yes |
| Europe | European List of Notified Chemical Substances (ELINCS) | No |
| Japan | Inventory of Existing and New Chemical Substances (ENCS) | No |
| Korea | Existing Chemicals List (ECL) | Yes |
| New Zealand | New Zealand Inventory | Yes |
| Philippines | Philippine Inventory of Chemicals and Chemical Substances (PICCS) | Yes |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | Yes |

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

| Issue date | 05-07-2015 |
|----------------------|--|
| Revision date | 11-03-2015 |
| Version # | 05 |
| HMIS® ratings | Health: 2* Flammability: 4 Physical hazard: 0 |
| NFPA ratings | Health: 2 Flammability: 4 Instability: 0 |
| NFPA ratings | |
| Disclaimer | The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. |
| Revision Information | Physical & Chemical Properties: Multiple Properties Transport Information: Material Transportation Information |