CRC.

SAFETY DATA SHEET

1. Identification

Product identifier Universal 2-Cycle Oil

Other means of identification

Product code SL2261, SL2262
Recommended use 2-Cycle engine oil
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

Company name CRC Industries, Inc.

Address 885 Louis Dr.

Warminster, PA 18974 US

Telephone

General Information 215-674-4300 **Technical** 800-521-3168

Assistance

 Customer Service
 800-272-4620

 24-Hour Emergency
 800-424-9300 (US)

(CHEMTREC) 703-527-3887 (International)
Website www.crcindustries.com

2. Hazard(s) identification

Physical hazards Flammable liquids Category 4

Health hazards Not classified.

Environmental hazards Hazardous to the aquatic environment, acute Category 3

hazard

Hazardous to the aquatic environment, Category 3

long-term hazard

OSHA defined hazards Not classified.

Label elements

Hazard symbol None.

Signal word Warning

Hazard statement Combustible liquid. Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use with adequate

ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. Wear protective gloves/eye protection/face protection. Avoid release

to the environment.

Response In case of fire: Do not use water jet as an extinguisher, as this will spread the fire.

Storage Store in a well-ventilated place. Keep cool.

Disposal Dispose of contents/container in accordance with local/regional/national regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	<u></u>
Distillates (petroleum), solvent-refined heavy naphthenic		64741-96-4	50 - 60
Residual oils (petroleum), solvent-dewaxed		64742-62-7	30 - 40

Chemical name	Common name and synonyms	CAS number	%
Stoddard Solvent		8052-41-3	10 - 20
Mineral oil		Mixture	3 - 5
Naphthalene		91-20-3	< 0.2

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation

If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. If breathing stops, provide artificial respiration. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If inhalation of a large amount does occur, call a physician immediately.

Skin contact

Wash off with plenty of water. Remove and isolate contaminated clothing and shoes. Get medical attention if irritation develops and persists. Wash contaminated clothing before reuse.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

If ingestion of a large amount does occur, call a poison control center immediately. Rinse mouth. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Never give anything by mouth to a victim who is unconscious or is having convulsions. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delaved

Direct contact with eyes may cause temporary irritation. Prolonged or repeated skin contact may cause irritation.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically.

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Dry chemical powder. Carbon dioxide (CO2). Water fog. Foam.

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

The product is combustible, and heating may generate vapors which may form explosive vapor/air mixtures. Runoff to sewer may create fire or explosion hazard. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire-fighting equipment/instructions General fire hazards

Containers should be cooled with water to prevent vapor pressure build up. Move containers from fire area if you can do so without risk.

Combustible liquid.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Avoid inhalation of vapors or mists. Do not touch or walk through spilled material. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. The product is immiscible with water and will spread on the water surface.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Use non-sparking tools and explosion-proof equipment. Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.

7. Handling and storage

Precautions for safe handling

Keep away from open flames, hot surfaces and sources of ignition. When using, do not eat, drink or smoke. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Avoid contact with eyes, skin, and clothing. Avoid breathing mist or vapor. Provide adequate ventilation. Use non-sparking tools and explosion-proof equipment. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Avoid release to the environment. Use care in handling/storage. For product usage instructions, please see the product label.

Conditions for safe storage, including any incompatibilities

Eliminate sources of ignition. Keep away from heat, sparks and open flame. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Components	Туре	Value	
Mineral oil	TWA	5 mg/m3	
US. OSHA Table Z-1 Limits for Air Co	ntaminants (29 CFR 1910.1000)		
Components	Туре	Value	Form
Distillates (petroleum), solvent-refined heavy naphthenic (CAS 64741-96-4)	PEL	5 mg/m3	Mist.
		2000 mg/m3	
		500 ppm	
Naphthalene (CAS 91-20-3)	PEL	50 mg/m3	
. ,		10 ppm	
Stoddard Solvent (CAS 8052-41-3)	PEL	2900 mg/m3	
,		500 ppm	
ACGIH			
Components	Туре	Value	Form
Mineral oil	TWA	5 mg/m3	Inhalable fraction
US. ACGIH Threshold Limit Values			
Components	Туре	Value	Form
Distillates (petroleum), solvent-refined heavy naphthenic (CAS 64741-96-4)	TWA	5 mg/m3	Inhalable fraction.
Naphthalene (CAS 91-20-3)	TWA	10 ppm	
Residual oils (petroleum), solvent-dewaxed (CAS 64742-62-7)	TWA	5 mg/m3	Inhalable fraction.
Stoddard Solvent (CAS 8052-41-3)	TWA	100 ppm	
U.S NIOSH			
Components	Туре	Value	Form
Mineral oil	STEL	10 mg/m3	Mist
	TWA	5 mg/m3	Mist
US. NIOSH: Pocket Guide to Chemica	al Hazards		
Components	Туре	Value	Form
Distillates (petroleum), solvent-refined heavy naphthenic (CAS 64741-96-4)	Ceiling	1800 mg/m3	
•	STEL	10 mg/m3	Mist.

Material name: Universal 2-Cycle Oil

SDS US

SL2261, SL2262 Version #: 01 Issue date: 05-30-2015

US. NIOSH: Pocket Guide to Chemical Hazards			
Components	Туре	Value Form	
Naphthalene (CAS 91-20-3)	STEL	75 mg/m3	
		15 ppm	
	TWA	50 mg/m3	
		10 ppm	
Stoddard Solvent (CAS 8052-41-3)	Ceiling	1800 mg/m3	
0002 11 0)	TWA	350 mg/m3	

No biological exposure limits noted for the ingredient(s). **Biological limit values**

Exposure guidelines

US ACGIH Threshold Limit Values: Skin designation

Naphthalene (CAS 91-20-3) Can be absorbed through the skin.

Appropriate engineering

controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Wear safety glasses with side shields (or goggles). Eye/face protection

Skin protection

Hand protection Wear protective gloves such as: Nitrile. Polyvinyl chloride (PVC).

Wear suitable protective clothing. Other

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a Respiratory protection

NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to

determine actual employee exposure levels.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Liquid. **Physical state** Liquid. **Form** Blue. Color

Odor Mild petroleum. **Odor threshold** Not available. Not available.

-94 °F (-70 °C) estimated Melting point/freezing point Initial boiling point and boiling 302 °F (150 °C) estimated

range

150 °F (65.6 °C) Cleveland Open Cup Flash point

Evaporation rate Slow.

Not available. Flammability (solid, gas) Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

0.9 % estimated

Flammability limit - upper

(%)

6 % estimated

2 hPa estimated Vapor pressure Vapor density > 1 (air = 1)0.88 - 0.9Relative density

SL2261, SL2262 Version #: 01 Issue date: 05-30-2015

Solubility (water) Insoluble.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 450 °F (232.2 °C) estimated

Decomposition temperature Not available.

Viscosity (kinematic) 75 cSt (104 °F (40 °C))

Percent volatile 65 % estimated

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Do not cut, weld, solder, drill, grind, or

expose containers to heat, flame, sparks, or other sources of ignition. Contact with incompatible

materials.

Incompatible materials
Hazardous decomposition

products

Carbon oxides. Sulfur oxides.

Strong oxidizing agents.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact Prolonged skin contact may cause temporary irritation. **Eye contact** Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity Not available.

Product Species Test Results

Universal 2-Cycle Oil

<u>Acute</u> Dermal

LD50 Rabbit 6061 mg/kg estimated

Inhalation

LC50 Rat 37 mg/l, 4 hours estimated

Oral

LD50 Rat 7244 mg/kg estimated

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation. **Serious eye damage/eye** Direct contact with eyes may cause temporary irritation.

irritation

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Stoddard Solvent (CAS 8052-41-3) 3 Not classifiable as to carcinogenicity to humans.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

SL2261, SL2262 Version #: 01 Issue date: 05-30-2015

^{*} Estimates for product may be based on additional component data not shown.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Not an aspiration hazard. **Aspiration hazard**

Prolonged inhalation may be harmful. **Chronic effects**

12. Ecological information

otoxicity	Harmful to	o aquatic life with long lasting effects.	
Product		Species Test Results	
Universal 2-Cycle Oil			
Aquatic			
Acute			
Crustacea	EC50	Daphnia	1090 mg/l, 48 hours estimated
Fish	LC50	Fish	70.8822 mg/l, 96 hours estimated
Components		Species	Test Results
Mineral oil			
Aquatic			
Acute			
Fish	LC50	Bluegill (Lepomis macrochirus)	2.2 mg/l, 96 hours
Naphthalene (CAS 91	-20-3)		
Aquatic			
Acute			
Crustacea	EC50	Water flea (Daphnia magna)	1.09 - 3.4 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	1.6 mg/l, 96 hours

^{*} Estimates for product may be based on additional component data not shown.

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Naphthalene 3.3 Stoddard Solvent 3.16 - 7.15

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal of waste from residues / unused products This product is not a RCRA hazardous waste (See 40 CFR Part 261.20 - 261.33). Empty containers may be recycled. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in accordance with all applicable regulations.

Hazardous waste code

Not regulated.

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

SARA 304 Emergency release notification

Not regulated.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

CERCLA Hazardous Substances: Reportable quantity

Not listed.

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Food and Drug Not regulated.

Administration (FDA)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

No

Section 311/312 Immediate Hazard - No Delayed Hazard - No **Hazard categories** Fire Hazard - Yes Pressure Hazard - No

Reactivity Hazard - No

SARA 302 Extremely hazardous substance

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Distillates (petroleum), solvent-refined heavy naphthenic (CAS 64741-96-4) Naphthalene (CAS 91-20-3)

Residual oils (petroleum), solvent-dewaxed (CAS 64742-62-7)

Stoddard Solvent (CAS 8052-41-3)

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. New Jersey Worker and Community Right-to-Know Act

Stoddard Solvent (CAS 8052-41-3)

Distillates (petroleum), solvent-refined heavy naphthenic (CAS 64741-96-4)

Naphthalene (CAS 91-20-3)

US. Massachusetts RTK - Substance List

Distillates (petroleum), solvent-refined heavy naphthenic (CAS 64741-96-4)

Stoddard Solvent (CAS 8052-41-3)

US. Pennsylvania Worker and Community Right-to-Know Law

Naphthalene (CAS 91-20-3)

Stoddard Solvent (CAS 8052-41-3)

SL2261, SL2262 Version #: 01 Issue date: 05-30-2015

US. Rhode Island RTK

None.

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Naphthalene (CAS 91-20-3) Listed: April 19, 2002

Volatile organic compounds (VOC) regulations

EPA

VOC content (40 CFR

51.100(s))

Not determined

Consumer products

(40 CFR 59, Subpt. C)

Not regulated

State

Not regulated Consumer products 14 % VOC content (CA) 14 % VOC content (OTC)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Toxic Substances Control Act (TSCA) Inventory

16. Other information, including date of preparation or last revision

Issue date 05-30-2015 Prepared by Allison Cho

Version # 01

United States & Puerto Rico

Not available. **Further information HMIS®** ratings Health: 1 Flammability: 2 Physical hazard: 0

Personal protection: B

Health: 1 NFPA ratings

Flammability: 2 Instability: 0

NFPA ratings



Disclaimer

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries.

Material name: Universal 2-Cycle Oil SDS US

Yes