

#### 02 2 %;CO2 12 %;Ar 86 %

 Issue Date:
 04.07.2013

 Last revised date:
 13.08.2015

Version: 2.0

Argoshield Universal (Welding mixture ISO14175-M24- ArCO-12/2)

SDS No.: 000010021887 1/13

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name:

02 2 %;CO2 12 %;Ar 86 %

#### Trade name:

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses:	Industrial and professional. Perform risk assessment prior to use. Shielding gas in gas welding. Consumer use.
	Shielding gas in gas welding.
Uses advised against	Uses other than those listed above are not supported. Contact supplier for more information on uses.

### 1.3 Details of the supplier of the safety data sheet

Supplier	
BOC	Telephone: 0800 111 333
Priestley Road, Worsley	-
M28 2UT Manchester	

E-mail: ReachSDS@boc.com

### 1.4 Emergency telephone number: 0800 111 333

### **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

Classification according to Directive 67/548/EEC or 1999/45/EC as amended.

Not classified

### Classification according to Regulation (EC) No 1272/2008 as amended.

### **Physical Hazards**

Gases under pressure

Compressed gas H280: Contains gas under pressure; may explode if heated.

2.2 Label Elements



Signal Words: Warning

Hazard Statement(s): H280: Contains gas under pressure; may explode if heated.



### 02 2 %;CO2 12 %;Ar 86 %

Issue Date: Last revised date:	04.07.2013 13.08.2015	Version: 2.0	SDS No.: 000010021887 2/13
Precautionary	Statement		
Prevention:	None.		
Response:	None.		
Storage:	P403: Store	in a well-ventilated place.	
Disposal:	None.		
Supplemental	label information EIGA-As: As	phyxiant in high concentrations.	
2.3 Other hazards:	None.		

# SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical name	Chemical formula	Concentration	CAS-No.	EC No.	REACH Registration No.	Notes
Carbon dioxide	CO2	12%	124-38-9	204-696-9	Listed in Annex IV/V of Regulation (EC) No 1907/2006 (REACH), exempted from registration.	#
Argon	Ar	86%	7440-37-1	231-147-0	Listed in Annex IV/V of Regulation (EC) No 1907/2006 (REACH), exempted from registration.	
oxygen	02	2%	7782-44-7	231-956-9	Listed in Annex IV/V of Regulation (EC) No 1907/2006 (REACH), exempted from registration.	

The concentrations of the components in the SDS header, product name on page one and in section 3.2 are in mol due to regulatory requirements. All concentrations are nominal.

# This substance has workplace exposure limit(s). PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

## Classification

Chemical name	Classificati	Classification	
Carbon dioxide	DSD:	none	
	CLP:	Press. Gas Liquef. Gas;H280	
Argon	DSD:	none	
	CLP:	Press. Gas Compr. Gas;H280	
oxygen	DSD:	O; R8	
	CLP:	Oxid. Gas 1;H270, Press. Gas Compr. Gas;H280	

DSD: Directive 67/548/EEC. CLP: Regulation No. 1272/2008.



### 02 2 %;CO2 12 %;Ar 86 %

 Issue Date:
 04.07.2013
 Version: 2.0
 SDS

 Last revised date:
 13.08.2015
 SDS
 SDS

SDS No.: 000010021887 \_\_\_\_\_\_3/13

The full text for all R-phrases and H-statements is displayed in section 16.

SECTION 4: First Aid Measures	
General:	In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.
4.1 Description of first aid measures	
Inhalation:	In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped. Low concentrations of CO2 cause increased respiration and headache.
Eye contact:	Adverse effects not expected from this product.
Skin Contact:	Adverse effects not expected from this product.
Ingestion:	Ingestion is not considered a potential route of exposure.
4.2 Most important symptoms and effects, both acute and delayed:	Respiratory arrest.
-	ical attention and special treatment needed
4.3 Indication of any immediate med Hazards:	ical attention and special treatment needed None.
-	-
Hazards: Treatment:	None.
Hazards: Treatment:	None.
Hazards: Treatment: SECTION 5: Firefighting Measures	None.
Hazards: Treatment: SECTION 5: Firefighting Measures General Fire Hazards: 5.1 Extinguishing media	None. None. Heat may cause the containers to explode. Material will not burn. In case of fire in the surroundings: use appropriate
Hazards: Treatment: SECTION 5: Firefighting Measures General Fire Hazards: 5.1 Extinguishing media Suitable extinguishing media: Unsuitable extinguishing	None. None. Heat may cause the containers to explode. Material will not burn. In case of fire in the surroundings: use appropriate extinguishing agent.



## 02 2 %;CO2 12 %;Ar 86 %

	02	2 70,002 12 70,AI 00 70	
Issue Date: Last revised date:	04.07.2013 13.08.2015	Version: 2.0	SDS No.: 000010021887 4/13
5.3 Advice for firefighters			
Special fire fighting procedures:	position u	fire: Stop leak if safe to do so. Contin ntil container stays cool. Use extingu e of the fire or let it burn out.	
Special protective equ for firefighters:	Special protective equipment for firefighters: Firefighters must use standard protective equipment including flame r coat, helmet with face shield, gloves, rubber boots, and in enclosed sp Guideline: EN 469 Protective clothing for firefighters. Performance req for protective clothing for firefighting. EN 15090 Footwear for firefight Protective gloves for firefighters. EN 443 Helmets for fire fighting in bu other structures. EN 137 Respiratory protective devices - Self-containe circuit compressed air breathing apparatus with full face mask - Requir testing, marking.		oots, and in enclosed spaces, SCBA. ghters. Performance requirements 00 Footwear for firefighters. EN 659 ets for fire fighting in buildings and e devices - Self-contained open-
SECTION 6: Accidental Re	lease Measures		
6.1 Personal precautions, protective equipment emergency procedure	and basement s: Wear self- is proved contained	area. Provide adequate ventilation. F s and workpits, or any place where it contained breathing apparatus wher to be safe. Guideline EN 137 Respirat open-circuit compressed air breathin ents, testing, marking.	ts accumulation can be dangerous. n entering area unless atmosphere cory protective devices - Self-
6.2 Environmental Precaut	ions: Prevent fu	rther leakage or spillage if safe to do	) SO.
6.3 Methods and material containment and clear		dequate ventilation.	
6.4 Reference to other sec	tions: Refer to se	ections 8 and 13.	



### 02 2 %;C02 12 %;Ar 86 %

Issue Date:04.07.2013Version: 2.0Last revised date:13.08.2015

SDS No.: 000010021887 5/13

## SECTION 7: Handling and Storage:

7.1 Precautions for safe handling:	Only experienced and properly instructed persons should handle gases under pressure. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Refer to supplier's handling instructions. The substance must be handled in accordance with good industrial hygiene and safety procedures. Protect containers from physical damage; do not drag, roll, slide or drop. Do not remove or deface labels provided by the supplier for the identification of the container contents. When moving containers, even for short distances, use appropriate equipment eg. trolley, hand truck, fork truck etc. Secure cylinders in an upright position at all times, close all valves when not in use. Provide adequate ventilation. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Avoid suckback of water, acid and alkalis. Keep container below 50°C in a well ventilated place. Observe all regulations and local requirements regarding storage of containers. When using do not eat, drink or smoke. Store in accordance with local/regional/national/international regulations. Never use direct flame or electrical heating devices to raise the pressure of a container. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. Damaged valves should be reported immediately to the supplier Close container valve after each use and when empty, even if still connected to equipment. Never attempt to repair or modify container valves or safety relief devices. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Keep container valve outlets clean and free from contaminates particularly oil and water. If user experiences any difficulty operating container valve discontinue use and contact supplier. Never attempt to transfer gases from one container to another. Container valve guards or caps should be in place.
7.2 Conditions for safe storage, including any incompatibilities:	Containers should not be stored in conditions likely to encourage corrosion. Stored containers should be periodically checked for general conditions and leakage. Container valve guards or caps should be in place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible material.
7.3 Specific end use(s):	None.

SECTION 8: Exposure Controls/Personal Protection

### 8.1 Control Parameters

### **Occupational Exposure Limits**

Chemical name	type	Exposure Limi	t Values	Source
Carbon dioxide	TWA	5,000 ppm	9,150	UK. EH40 Workplace Exposure Limits
			mg/m3	(WELs) (12 2011)
	STEL	15,000 ppm	27,400	UK. EH40 Workplace Exposure Limits
			mg/m3	(WELs) (12 2011)
	TWA	5,000 ppm	9,000	EU. Indicative Exposure Limit Values in
			mg/m3	Directives 91/322/EEC, 2000/39/EC,
				2006/15/EC, 2009/161/EU (12 2009)



### 02 2 %;C02 12 %;Ar 86 %

	l l	JZ Z %;UUZ TZ %;Af 86 %	
Issue Date:	04.07.2013	Version: 2.0	SDS No.: 000010021887
Last revised date:	13.08.2015		6/13
8.2 Exposure controls			
Appropriate engine controls:	air venti extractio exceede released Preferat drink or	r a work permit system e.g. for mainten lation. Provide adequate ventilation, in on, to ensure that the defined occupatio ed. Oxygen detectors should be used wild d. Systems under pressure should be regoly use permanent leak tight connection smoke when using the product.	ncluding appropriate local onal exposure limit is not hen asphyxiating gases may be gularly checked for leakages.
individual protectio	on measures, such as pe	rsonal protective equipment	
General information	assess ti matches Keep se Persona	A risk assessment should be conducted and documented in each work area assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be consid Keep self contained breathing apparatus readily available for emergency us Personal protective equipment for the body should be selected based on the being performed and the risks involved.	
Eye/face protection		Wear eye protection to EN 166 when using gases. Guideline: EN 166 Personal Eye Protection.	
Skin protection			
Hand Protection		orking gloves while handling containers he: EN 388 Protective gloves against me	
<b>Body protection</b>	: No spec	ial precautions.	
Other:		Wear safety shoes while handling containers Guideline: ISO 20345 Personal protective equipment - Safety footwear.	
<b>Respiratory Protect</b>	tion: Not requ	lired.	
Thermal hazards:	No preca	autionary measures are necessary.	
Hygiene measures		risk management measures are not req and safety procedures. Do not eat, drir	
Environmental expo controls:	osure For wast	te disposal, see section 13.	

# **SECTION 9: Physical And Chemical Properties**

## 9.1 Information on basic physical and chemical properties

Appearance	
Physical state:	Gas
Form:	Compressed gas
Colour:	CO2: Colourless Ar: Colourless
	O2: Colourless
Odour:	CO2: Odourless



# 02 2 %;CO2 12 %;Ar 86 %

04.07.2013	Version: 2.0	SDS No.: 000010021887
13.08.2015		7/13

	O2: Odourless Ar: Odourless	
Odour Threshold:	Odour threshold is subjective and is inadequate to warn of over exposure.	
pH:	not applicable.	
Melting Point:	No data available.	
Boiling Point:	No data available.	
Sublimation Point:	not applicable.	
Critical Temp. (°C):	No data available.	
Flash Point:	Not applicable to gases and gas mixtures.	
Evaporation Rate:	Not applicable to gases and gas mixtures.	
Flammability (solid, gas):	This product is not flammable.	
Flammability limit - upper (%):	not applicable.	
Flammability limit - lower(%):	not applicable.	
Vapour pressure:	No reliable data available.	
Vapour density (air=1):	1.42 (calculated) (15 °C)	
Relative density:	No data available.	
Solubility(ies)		
Solubility in Water:	No data available.	
Partition coefficient (n-octanol/water):	Not known.	
Autoignition Temperature:	not applicable.	
Decomposition Temperature:	Not known.	
Viscosity		
Kinematic viscosity:	No data available.	
Dynamic viscosity:	No data available.	
Explosive properties:	Not applicable.	
Oxidising Properties:	not applicable.	
9.2 Other information:	Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.	

# SECTION 10: Stability and Reactivity

10.1 Reactivity:	No reactivity hazard other than the effects described in sub-section below.
10.2 Chemical Stability:	Stable under normal conditions.
10.3 Possibility of Hazardous Reactions:	None.
10.4 Conditions to Avoid:	None.
10.5 Incompatible Materials:	No reaction with any common materials in dry or wet conditions.
10.6 Hazardous Decomposition Products:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.



## 02 2 %;CO2 12 %;Ar 86 %

		0, CUZ IZ /0, AI OU /0	
e Date:	04.07.2013	Version: 2.0	SDS No.: 0000100218
revised date:	13.08.2015		8/
ION 11: Toxicologi	al Information		
General informatio	n: None.		
1 Information on toxi	cological effects		
Acute toxicity - Ora Product		ilable data, the classification cri	iteria are not met.
Acute toxicity - Der Product		ilable data, the classification cri	iteria are not met.
Acute toxicity - Inh Product		ed for acute toxicity based	on available data.
Skin Corrosion/Irrit Product		lable data, the classification cri	teria are not met.
Serious Eye Damag Product	-	lable data, the classification cri	teria are not met.
Respiratory or Skin Product		lable data, the classification cri	teria are not met.
Germ Cell Mutagen Product		lable data, the classification cri	teria are not met.
Carcinogenicity Product	Based on avail	lable data, the classification cri	teria are not met.
Reproductive toxic Product	-	lable data, the classification cri	teria are not met.
Specific Target Org Product	<b>in Toxicity - Single Exposure</b> Based on avail	able data, the classification cri	teria are not met.
Specific Target Org Product	<b>in Toxicity - Repeated Expos</b> Based on avail	s <b>ure</b> lable data, the classification cri	teria are not met.
Aspiration Hazard Product	Not applicable	e to gases and gas mixtures	

## **SECTION 12: Ecological Information**

# 12.1 Toxicity

Acute toxicity Product

No ecological damage caused by this product.



## 02 2 %;CO2 12 %;Ar 86 %

Issue Date:	04.07.2013	Version: 2.0	SDS No.: 000010021887
Last revised date:	13.08.2015		9/13
12.2 Persistence and De Product		licable to gases and gas mixtures	
12.3 Bioaccumulative P Product	The pro	duct is expected to biodegrade and is no in an aquatic environment.	ot expected to persist for long
12.4 Mobility in Soil Product		Because of its high volatility, the product is unlikely to cause ground or water pollution.	
12.5 Results of PBT and assessment Product		sified as PBT or vPvB.	
12.6 Other Adverse Effe	ects:		
Global Warming P	Global v	varming potential: 0.1 ischarged in large quantities may contri	bute to the greenhouse effect.
Component info Carbon dioxide		varming potential: 1	

## SECTION 13: Disposal Considerations

### 13.1 Waste treatment methods

General information:	Do not discharge into any place where its accumulation could be dangerous. Vent to atmosphere in a well ventilated place.		
Disposal methods:	Refer to the EIGA code of practice (Doc.30 "Disposal of Gases", downloadable at http://www.eiga.org) for more guidance on suitable disposal methods. Dispose of container via supplier only. Discharge, treatment, or disposal may be subject to national, state, or local laws.		
<u>European Waste Codes</u> Container:	16 05 05: Gases in pressure containers other than those mentioned in 16 05 04.		



### 02 2 %;CO2 12 %;Ar 86 %

 Issue Date:
 04.07.2013

 Last revised date:
 13.08.2015

Version: 2.0

SDS No.: 000010021887 10/13

# SECTION 14: Transport Information

ADR	
14.1 UN Number:	UN 1956
14.2 UN Proper Shipping Name: 14.3 Transport Hazard Class(es)	COMPRESSED GAS, N.O.S. (Argon, Carbon Dioxide)
Class:	2
Label(s):	2.2
Hazard No. (ADR):	20
Tunnel restriction code:	(E)
Emergency Action Code: 14.4 Packing Group:	2TE
14.5 Environmental hazards:	- not applicable
14.6 Special precautions for user:	-
RID 14.1 UN Number:	UN 1956
14.2 UN Proper Shipping Name	COMPRESSED GAS, N.O.S. (Argon, Carbon Dioxide)
14.3 Transport Hazard Class(es)	
Class:	2
Label(s):	2.2
14.4 Packing Group: 14.5 Environmental hazards:	-
14.5 Environmental hazards. 14.6 Special precautions for user:	not applicable
IMDG	
14.1 UN Number:	UN 1956
14.2 UN Proper Shipping Name: 14.3 Transport Hazard Class(es)	COMPRESSED GAS, N.O.S. (Argon, Carbon Dioxide)
Class:	2.2
Label(s):	2.2
EmS No.:	F-C, S-V
14.3 Packing Group:	-
14.5 Environmental hazards:	not applicable
14.6 Special precautions for user:	-
ΙΑΤΑ	
14.1 UN Number:	UN 1956
14.2 Proper Shipping Name: 14.3 Transport Hazard Class(es):	Compressed gas, n.o.s. (Argon, Carbon Dioxide)
Class:	2.2
Label(s):	2.2
14.4 Packing Group:	-
14.5 Environmental hazards:	not applicable
14.6 Special precautions for user:	-
Other information Passenger and cargo aircraft:	Allowed.
Cargo aircraft only:	Allowed.
5 5	

14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: not applicable



### 02 2 %;CO2 12 %;Ar 86 %

Issue Date:	04.07.2013	Version: 2.0	SDS No.: 000010021887
Last revised date:	13.08.2015		11/13
Additional id	entification:	Avoid transport on vehicles where the I the driver's compartment. Ensure vehic hazards of the load and knows what to an emergency. Before transporting prod are firmly secured. Ensure that the cont leaking. Container valve guards or caps adequate air ventilation.	le driver is aware of the potential do in the event of an accident or duct containers ensure that they ainer valve is closed and not

#### SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

#### **EU Regulations**

Directive 96/61/EC: concerning integrated pollution prevention and control (IPPC): Article 15, European Pollution Emission Registry (EPER):

Chemical name	CAS-No.	Concentration
Carbon dioxide	124-38-9	10 - 20%

#### Directive 96/82/EC (Seveso II): on the control of major accident hazards involving dangerous substances:

Chemical name	CAS-No.	Concentration
oxygen	7782-44-7	1.0 - 10%

#### Directive 98/24/EC on the protection of workers from the risks related to chemical agents at work:

Chemical name	CAS-No.	Concentration
oxygen	7782-44-7	1.0 - 10%

#### National Regulations

Management of Health and Safety at Work Regulations (1999 No. 3242). The Regulatory Reform (Fire Safety) Order 2005 (2005 No. 1541). Control of Substances Hazardous to Health Regulations (COSHH, 2002 No. 2677). Provision and Use of Work Equipment Regulations (PUWER, 1998 No. 2306). Personal Protective Equipment Regulations (1992 No. 2966). Control of Major Accident Hazards Regulations (COMAH, 2015 No. 483). Pressure Systems Safety Regulations (PSSR, 2000 No. 128). Only products that comply with the food regulations (EC) No. 1333/2008 and (EU) No. 231/2012 and are labelled as such may be used as food additives. This Safety Data Sheet has been produced to comply with Regulation (EU) 453/2010.

**15.2 Chemical safety assessment:** No Chemical Safety Assessment has been carried out.

### SECTION 16: Other Information

**Revision Information:** Not relevant.



# 02 2 %;CO2 12 %;Ar 86 %

Issue Date: Last revised date:	04.07.2013 13.08.2015	Version: 2.0	SDS No.: 000010021887 12/13			
Key literature reference		purces of data have been used in the con	npliation of this SDS, they include			
sources for data:		ot exclusive to:	(1			
	0,	or Toxic Substances and Diseases Registry	y (AISDR)			
		/ww.atsdr.cdc.gov/).				
		European Chemical Agency: Guidance on the Compilation of Safety Data Sheets.				
		European Chemical Agency: Information on Registered Substances				
		http://apps.echa.europa.eu/registered/registered-sub.aspx#search				
		European Industrial Gases Association (EIGA) Doc. 169 Classification and Labelling				
	guide.					
		onal Programme on Chemical Safety (http:				
		5:2010 Gases and gas mixtures - Determ				
	oxidizing	ability for the selection of cylinder valve	outlets.			
	Mathesor	n Gas Data Book, 7th Edition.				
	National I	nstitute for Standards and Technology (N	NIST) Standard Reference Database			
	Number 6	9.				
	The ESIS (	The ESIS (European chemical Substances 5 Information System) platform of the				
	former Eu	former European Chemicals Bureau (ECB) ESIS (http://ecb.jrc.ec.europa.eu/esis/).				
	The Europ	The European Chemical Industry Council (CEFIC) ERICards.				
	United Sta	United States of America's National Library of Medicine's toxicology data network				
	TOXNET (ł	TOXNET (http://toxnet.nlm.nih.gov/index.html)				
	Threshold	Threshold Limit Values (TLV) from the American Conference of Governmental				
	Industrial	Industrial Hygienists (ACGIH).				
	Substance	Substance specific information from suppliers.				
		Details given in this document are believed to be correct at the time of publication.				
		EH40 (as amended) Workplace exposure limits.				
Wording of the R-phrase	s and H-statements in	n sections 2 and 3				
the angle the teph as	H270	May cause or intensify fire; oxidise	٥r			
	H280	Contains gas under pressure; may				
	R8	Contact with combustible material				
	No					
Training information:	Users of b	reathing apparatus must be trained. The	hazard of asphyxiation is often			
-	overlooke	overlooked and must be stressed during operator training. Ensure operators				
	understar	understand the hazards.				
Classification according	to Regulation (FC) No	1272/2008 as amended.				
olassification according	-	s Compr. Gas, H280				
Other information:		ing this product in any new process or e>				
		compatibility and safety study should be carried out. Ensure adequate air ventilation.				
		Ensure all national/local regulations are observed. Whilst proper care has been				
		taken in the preparation of this document, no liability for injury or damage resulting				
		se can be accepted. Note: When the Proc				
	header th	e decimal sign and its position comply w	ith rules for the structure and			
		f international standards, and is a comm				
		is two (to three decimal places) and not two thousand, whilst 1.000 is one thousand				
		ne (to three decimal places).				
		· · · ·				



## 02 2 %;C02 12 %;Ar 86 %

Issue Date:	04.07.2013	Version: 2.0	SDS No.: 000010021887
Last revised date:	13.08.2015		13/13

Last revised date: Disclaimer: 13.08.2015

This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.