# **MATERIAL SAFETY DATA SHEET**

### SECTION 1 - IDENTIFICATION OF SUBSTANCE & COMPANY PREPARING INFORMATION

**Identity:** G6 Midnight Black

Manufacturer's Name: Minnesota Clay

Address: 2960 Niagara Lane, Plymouth MN 55447

Tel Phone: (763) 432-0875 Emergency Tel: None

Date Prepared: July 29, 2011 Replaces MSDS dated: N/A

# **SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS**

| INGREDIENTS     | CAS<br>NUMBER | EXPOSURE LIMITS (mg/m³) |       | LD <sub>50</sub><br>mg/kg | LC <sub>50</sub><br>mg/m <sup>3</sup> |
|-----------------|---------------|-------------------------|-------|---------------------------|---------------------------------------|
|                 |               | PEL                     | TLV   |                           |                                       |
| Clay/Kaolin     | 1332-58-7     | 15                      | 2     | NA                        | NA                                    |
| Silica (Quartz) | 14808-60-7    | 10mg/m <sup>3</sup>     | 0.025 | NA                        | NA                                    |
|                 |               | %Silica+2               |       |                           |                                       |
| Pigments        | Varies        | NA                      | NA    | NA                        | NA                                    |

#### SECTION 3 - HAZARD IDENTIFICATION

Primary Route of Entry - Inhalation (dry form only), ingestion and dermal.

Hazards - May cause skin and eye irritation, Lung effects including cancer, silicosis

### Silica, Crystalline (Quartz)

A single exposure will not result in serious adverse health effects.

Respirable crystalline silica (quartz) can cause silicosis, a fibrosis (scarring) of the lungs. Silicosis may be progressive; it may lead to disability and death. Crystalline silica (quartz) inhaled from occupational sources is classified as carcinogenic to humans. There are some studies that show excess numbers of cases of scleroderma and other connective tissue disorders in workers exposed to respirable crystalline silica. Silicosis increases the risk of tuberculosis. Some studies that show an increased incidence of chronic kidney disease and end-stage renal disease in workers exposed to respirable crystalline silica.

### Pigments (Stains)

Contains pigments which are produced from various metal salts, and/or other organic chemicals. Many of these pigments are in the form of spinel, which are formed by the reaction of these different metal salts at high temperature into essentially insoluble homogeneous pigment crystals. Spinels are considered of less hazardous than the individual metals they contain The pigments used may contain one or more of the following: silica (quartz), cobalt, vanadium, copper, iron, manganese, chromium and cadmium (encapsulated).

#### **SECTION 4 - FIRST-AID MEASURES**

Inhalation - Remove from exposure.

Dermal - Wash skin with soap and water.

Eye - Flush eyes with large quantities of water for at least 15 minutes. If

irritation is present after washing, contact a physician.

Ingestion- Do not induce vomiting, contact a physician.

#### SECTION 5 - FIRE-FIGHTING MEASURES

Special Fire-Fighting Procedure - None

Unusual Fire or Explosion Hazards - None

Extinguishing Media - None

Hazardous Combustion Products - Unknown

### **SECTION 6 - ACCIDENTAL RELEASE MEASURES**

Procedures for Leaks or Spills - place in suitable container, and provide adequate ventilation. Wear personnel protective equipment (Goggles, glove, personal protective clothing).

### **SECTION 7 - HANDLING AND STORAGE**

Engineer Control – use adequate ventilation

Procedure/Equipment - no specific requirement. See personal protective equipment.

Work Practices - use with adequate ventilation, avoid skin, eye and inhalation contact, wash hands

Storage - Store in tightly closed container. Store in a cool well-ventilated area.

## SECTION 8 - EXPOSURE CONTROL/PERSONAL PROTECTION

Engineering Measures – provide adequate ventilation

Personal Protective Equipment - wear chemical safety goggles, protective chemical resistant gloves, appropriate protective clothing

### **SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

Appearance - Powder Vapor Pressure - N/A

Explosive Properties - N/A Percent Volatile - N/A

Odor and Odor Threshold - N/A Vapor Density - N/A

Partition Coefficient - N/A Applicable Evaporation Rate - N/A

pH - N/A Melting/Softening Point - None

Oxidizing Properties - N/A Freezing Point - N/A

Boiling Point - N/A Specific Gravity - N/A

Solubility in Water - No Flash Point - N/A

### **SECTION 10 - STABILITY AND REACTIVITY**

Stability - Unknown
Hazardous Polymerization - None
Hazardous Decomposition Products - None
Conditions to Avoid - None
Incompatibility – Unknown

### **SECTION 11 - TOXICOLOGICAL INFORMATION**

Hazard to Humans - There is no toxicity data on this mixture. Likely to be a skin and eye irritant. Inhalation of dust may cause lung effects.

Animal Experiment - There is no toxicity data on this mixture

Acute – Likely to be a skin and eye irritant

Chronic/Other - Inhalation may cause lung effects. Contains quartz, which can cause silicosis and is a potential carcinogen.

### **SECTION 12 - ECOLOGICAL INFORMATION**

No specific information available.

### **SECTION 13 - DISPOSAL INFORMATION**

Dispose according to local regulations. No specific information available.

# **SECTION 14 - TRANSPORTATION INFORMATION**

No specific information available.

# **SECTION 15 - REGULATORY INFORMATION**

Ingredients are listed on TSCA, DSL and EINECS inventories.

Quartz is listed on IARC, NTP, OSHA and/or Calif. Prop 65 cancer lists.

No specific other information available.

# **SECTION 16 - OTHER INFORMATION**

Conforms to D 4236

No other specific information available.