MATERIAL SAFETY DATA SHEET

SECTION 1 - IDENTIFICATION OF SUBSTANCE & COMPANY PREPARING INFORMATION

Identity: HG-12 Metallic Green

Manufacturer's Name: Minnesota Clay

Address: 2960 Niagara Lane, Plymouth MN 55447

Tel Phone: (763) 432-0875 Emergency Tel: None

Date Prepared: July 29, 2011 Replaces MSDS dated: N/A

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENTS	CAS	EXPOSURE LIMITS		LD ₅₀	LC ₅₀
	NUMBER	(mg/m ³)		mg/kg	mg/m ³
		PEL	TLV		
Clay/Kaolin	1332-58-7	15	2	NA	NA
Silica (Quartz)	14808-60-7	10mg/m ³	0.025	NA	NA
		%Silica+2			
Calcium	1317-65-3	15	NA	6540	NA
Carbonate					
Zirconium	14940-68-2	NA	NA	NA	NA
Copper	7440-50-8	.1	.2	NA	NA
Compounds					

SECTION 3 - HAZARD IDENTIFICATION

Primary Route of Entry - Inhalation (dry form only), ingestion and dermal.

Hazards - May cause skin and eye irritation, Lung effects including cancer, silicosis

Silica, Crystalline (Quartz)

A single exposure will not result in serious adverse health effects.

Respirable crystalline silica (quartz) can cause silicosis, a fibrosis (scarring) of the lungs. Silicosis may be progressive; it may lead to disability and death. Crystalline silica (quartz) inhaled from occupational sources is classified as carcinogenic to humans. There are

some studies that show excess numbers of cases of scleroderma and other connective tissue disorders in workers exposed to respirable crystalline silica. Silicosis increases the risk of tuberculosis. Some studies that show an increased incidence of chronic kidney disease and end-stage renal disease in workers exposed to respirable crystalline silica.

Calcium Carbonate

Overexposure may result in irritation to eyes, skin and respiratory system. Chronic exposure may result in hyperclacemica, alkalosis, and renal impairment. Animal studies suggest that inhalation may enhance susceptibility to respiratory infection.

Zirconium or Zirconium Compounds

Skin, lung granulomas; in animals: irritation skin, mucous membrane; X-ray evidence of retention in lungs.

Copper or Copper Compounds

Overexposure can cause nausea, chills, diarrhea. May cause respiratory irritation, skin irritation (oxide pox), fever, eye irritation with redness, pain, and conjunctivitis; preexisting lung diseases may be aggravated by exposure. Could result in respiratory disease if over-exposed on a chronic basis.

SECTION 4 - FIRST-AID MEASURES

Inhalation - Remove from exposure.

Dermal - Wash skin with soap and water.

Eye - Flush eyes with large quantities of water for at least 15 minutes. If

irritation is present after washing, contact a physician.

Ingestion- Do not induce vomiting, contact a physician.

SECTION 5 - FIRE-FIGHTING MEASURES

Special Fire-Fighting Procedure - None

Unusual Fire or Explosion Hazards - None Extinguishing Media - None

Hazardous Combustion Products - Unknown

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Procedures for Leaks or Spills - place in suitable container, and provide adequate ventilation. Wear personnel protective equipment (Goggles, glove, personal protective clothing).

SECTION 7 - HANDLING AND STORAGE

Engineer Control – use adequate ventilation

Procedure/Equipment - no specific requirement. See personal protective equipment.

Work Practices - use with adequate ventilation, avoid skin, eye and inhalation contact, wash hands

Storage - Store in tightly closed container. Store in a cool well-ventilated area.

SECTION 8 - EXPOSURE CONTROL/PERSONAL PROTECTION

Engineering Measures – provide adequate ventilation

Personal Protective Equipment - wear chemical safety goggles, protective chemical resistant gloves, appropriate protective clothing

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance - Powder pH - N/A

Explosive Properties - N/A Oxidizing Properties - N/A

Odor and Odor Threshold - N/A Boiling Point - N/A

Partition Coefficient - N/A Solubility in Water - No

Vapor Pressure - N/A Freezing Point - N/A

Percent Volatile - N/A Specific Gravity - N/A

Vapor Density - N/A Flash Point - N/A

Applicable Evaporation Rate - N/A Flammable Limits - N/A

Melting/Softening Point - None Auto-Ignition Temperature - N/A

SECTION 10 - STABILITY AND REACTIVITY

Stability - Unknown
Hazardous Polymerization - None
Hazardous Decomposition Products - None
Conditions to Avoid - None
Incompatibility – Unknown

SECTION 11 - TOXICOLOGICAL INFORMATION

Hazard to Humans - There is no toxicity data on this mixture. Likely to be a skin and eye irritant. Inhalation of dust may cause lung effects.

Animal Experiment - There is no toxicity data on this mixture

Acute – Likely to be a skin and eye irritant

Chronic/Other - Inhalation may cause lung effects. Contains quartz, which can cause silicosis and is a potential carcinogen.

SECTION 12 - ECOLOGICAL INFORMATION

No specific information available.

SECTION 13 - DISPOSAL INFORMATION			
Dispose according to local regulations. No specific information available.			
SECTION 14 - TRANSPORTATION INFORMATION			
No specific information available.			
SECTION 15 - REGULATORY INFORMATION			
Ingredients are listed on TSCA, DSL and EINECS inventories.			
Quartz is listed on IARC, NTP, OSHA and/or Calif. Prop 65 cancer lists.			
No specific other information available.			
SECTION 16 - OTHER INFORMATION			
Conforms to D 4236			
No other specific information available.			